

ROTARY MOWER



SMRM-190H



SMRM-165



SMRM-210H



SMRM-125



SMRM-210H





GENERAL FEATURES

Rotary mower is used to cut grass, meadow grass, feed plants with blades rotating at a high speed existing on both of the 2 drums rotating reversely to each other. Cutting height adjusting function and high quality cutting provides to keep nutrient values of plants and drying is made possible in a short time. If it hits to hard and big objects (tree, stone, etc.), by moving backward, safety mechanism of the machine is protected against damages which may occur.

TECHNICAL DETAILS

CODE	TRANSPORT POSITION	WORKING WIDTH (MM)	NUMBER OF BLADES	DRUM SPEED (RPM)	WEIGHT (KG)	PTO ROTATION (RPM)	REQUIRED POWER (HP)
SMRM-125	MECHANICAL	1250	6	1920	275	540	MIN. 25
SMRM-145	MECHANICAL	1450	6	1920	300	540	MIN. 25
SMRM-165	MECHANICAL	1650	6	1920	360	540	MIN. 25
SMRM-190	MECHANICAL	1900	8	2500	405	540	MIN. 25
SMRM-165H	HYDRAULICAL	1650	6	1920	375	540	MIN. 25
SMRM-190H	HYDRAULICAL	1900	8	2500	420	540	MIN. 25
SMRM-210H	HYDRAULICAL	2100	8	3000	640	540	50-80





SOIL MASTER
AGRICULTURAL MACHINERY

HEAD OFFICE

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20
F: +90 332 290 00 19

www.soilmaster.com.tr

FACTORY

Add: Büyükkayacık Osb, Yaglacık Cd. No:
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85
T: +90 332 239 18 86
F: +90 332 239 18 87

 +90 (532) 137 01 74

 info@soilmaster.com.tr



For detailed information about
our products, you can scan the
QR code by your device.